

PRODUCT DATASHEET

GLOBAL TAG **PROTECTION CASE BEACONY (BLE)**



Global Tag **PROTECTION CASE BEACONY** is a BLE (Bluetooth Low Energy 4.2) based on Disk Beacony **Smart Beacon** designed for indoor/outdoor **IoT applications**.

- **Waterproof** protection case in silicone
- **ON/OFF button** with additional functions (**reset, alarm**)
- Battery **CR2032** replaceable
- Press-fit housing closure
- Up to **200m** detection distance
- **iBeacon** and **Eddystone** (UID, URL, TLM) compliant
- Sticker with Mac Address (and its QRcode) and Friendly Name on the beacon surface
- LED function for **Pick to Light**
- Optionally, **accelerometer, temperature/humidity sensor**
- Optionally, **NFC** integrated
- Choice between a wide range of Firmwares

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions: Ø36mm diameter / Ø1,417in diameter

Thickness: 15mm / 0.59in

Weight: 14gr (including battery)

Material: Silicone (external case) – Polycarbonate (internal case)

Color: Black (customized on request).

Class Protection: IP67

Battery type: CR2032 replaceable (Panasonic®).

Battery life: One year (with Broadcast Interval: 1 second and Tx Power: 0dB)

System-On-Chip (SoC): Nordic 52810

Storage Temperature: -15°C to +50°C / 5°F to +122°F

Operating Temperature: -15°C to +45°C / 5°F to +113°F

Delivery format: Singulated

Expected lifetime: Years in normal operating conditions

G-Sensor: ST Microelectronics mod. LIS3DH

Temperature/humidity sensor: Sensirion mod. SHT3x-DIS



ELECTRONIC AND OPERATIVE PARAMETERS

Operation Frequency: 2400-2483,5MHz

IEEE Standard: 802.15.1 (Bluetooth 4.2 Low Energy BLE)

Transmission distance: up to 200meters

Transmission Power: 4 different Level (-23dBm / -6dBm / 0dBm / +4dBm)

Default Broadcast Interval: 1s.

Broadcast interval: 100ms to 10000ms. (step of 100ms) – Except optional “Longer Broadcast Interval FW”

Support Operating System: iOS7.0 and Android 4.2+

Scan Response: Yes (max 31Byte Length), containing Battery level, Device name (11Byte), Sensors value

CUSTOMIZATION OPTIONS

Housing Printing : Logo printing or serial number laser engraving

Label on surface: Label can be customized according to customer's request

Setting / Encoding: Beacons services values can be pre-set as per customer's requirement (from xls file)

Available sensors: Accelerometer and/or temperature/humidity sensor

Firmware: Different FW are available, which can be uploaded on request

APPLICATION NOTE

Retail Marketing

Outdoor Asset Tracking

Indoor/Outdoor Positioning

Smart Guide for museums and theme parks

Maintenance

PRODUCT CODE AND ORDER INFORMATION

GT-PTCBY-BLE: Protection case Beacony without sensors

GT-PTCBY_A-BLE: Protection case Beacony with **accelerometer**

GT-PTCBY_TH_BLE: Protection case Beacony with **temperature/humidity sensor**

GT-PTCBY_ATH-BLE: Protection case Beacony with **accelerometer** and with **temperature/humidity sensor**

For any clarification, please do not hesitate to contact us at any time:

Global Tag Srl – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2019 - Global Tag Srl