

PRODUCT DATASHEET

GLOBAL TAG CUBIC-S BEACONY (BLE)



Global Tag **CUBIC-S BEACONY** is Rugged Beacon Bluetooth Low Energy (version 4.0 smart) for indoor and outdoor use. With adhesive is very easy way to attach on asset or container. With replaceable battery has very long reading range, up to 100meters.

Design to operate with iOS 7.0 and Android 4.3+ system.







MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions: 60x36x15mm / 2,83x1,77x0,87in

Mounting System: Adhesive 3M 467 Weight: 39gr. without battery

Material: ABS

Color: generally grey silver or black, available on demand other colors (MOQ can be request)

Class Protection: IP65

Battery type: 2pcs. CR2477 Battery. Replaceable.

Battery life: up to three years. **System-On-Chip (SoC):** nRF51822

Storage Temperature: -25°C to +50°C / -13°F to +122°F
Operating Temperature: -25°C to +50°C / -13°F to +122°F

Delivery format: Singulated

Expected lifetime: Years in normal operating conditions

ELECTRONIC AND OPERATIVE PARAMETERS

Operation Frequency: 2400-2483,5MHz

IEEE Standard: 802.15.1 (Bluetooth 4.0 Low Energy BLE)

Transmission distance: 100meters

Default Ping Rate: 900ms

Ping Rate interval: 100ms to 10000ms. (step of 100ms) **Support Operating System**: iOS7.0 and Android 4.3+

Accurate digital RSSI

UID NUMBER AND ADVERTISING PACKET

UID Address: 6 Byte Unique identifier

Advertising Size: 30bytes

Proximity UUID: 16bytes (including in advertising packet)

Major: 2bytes (including in advertising packet) **Minor**: 1byte (including in advertising packet)



CUSTOMIZATION OPTIONS
Silk Printing: printing logo or serial number
INSTALLATION MODE
With 3M Adhesive: when mounting the tag with adhesive background, clean and dry the surface for obtaining maximum bond strength.
APPLICATION NOTE
Tracking Container
Railways application
Marketing Management
Asset inventory
CERTIFICATIONS
iBeacon License
CE Regulations (Included EN300328, EN301489, EN60950, EM62479)
FCC Regulations (FCC Part 15)
ORDER INFORMATION
PRODUCT CODE CUBIC-S BEACONY: GT-CUSY-BLE
For printing options or for produce transponder with different color or with other type of customization contact us for more information:
Global Tag Srl – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy
P +39 030 2005259
S global-tag
W <u>www.global-tag.com</u>
M <u>sales@global-tag.com</u>

_ DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2016 - Global Tag Srl