

## **PRODUCT DATASHEET**

# **GLOBAL TAG ON-METAL STICKY**



Global Tag **ON-METAL STICKY**, UHF frequency, it's made for indoor environment where need to have a good performance, on-metal installation, very easy installation way and good performance with a small size.

Are available different customization as color mold, EPC encoding, serial number engraving and any other features on demand.








### **MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS**

**Dimensions**: 75x15x3mm / 3,34x0,79x0,12in



Mounting System: Adhesive (3M 300LSE)

Weight: 3gr.

Material: Laminated Label

**Color:** Generally red color – Available optionally any other colors

Class Protection: IP54 (Limited protection against dust ingress. (no harmful deposit), / Protection from splashed water)

Storage Temperature: -55°C (for 3h) to +100°C (for 2h) / -67°F (for 3h) to +230°F (for 2h) (for any other particular request contact us)

Operating Temperature: -25°C to +85°C / -13°F to +185°F

Weather Ability: Very Good, including UV resistance and sea water

**Delivery format:** Singulated

Expected lifetime: Years in normal operating conditions

Chemical resistance: No physical or performance changes with main detergent using to clean surface where transponder is installed

#### \_ CHIP SPECIFICATION AVAILABLE

	UHF 860-960MHz
Device type	Class 1 Gen 2
Air interface protocol	ISO18000-63
IC Type Available	Alien Higgs3, other on-request



Size Antenna	70x15mm
Read Range	Up to 3/4meters

_ C	US	TO	MIZ	ATIC	O NO	PTIO	NS
-----	----	----	-----	------	------	------	----

**Silk Printing**: serial progressive number from database, randomize number from database text and Barcode, 4-colors printing logo. Other customization on required.

**Pre-Encoding:** Customer specific encoding of EPC or User Memory (also from Database). Locking permanently or with password. Insert into Database TID code.

#### \_ INSTALLATION MODE

With 3M 300LSE Adhesive model: when mounting the tag with adhesive background, clean and dry the surface for obtaining maximum bond strength.

#### **APPLICATION NOTE**

**Assets management: ON-METAL STICKY** can be used to trace on-metal indoor company assets. Thanks to low price, small size but high performance is perfect tag.

**Maintenance On-Metal assets: ON-METAL STICKY** is tag to improve maintenance service with easy method to install on –metal surface for indoor environment.

## ORDER INFORMATION

Standard product is made with Alien Higgs3 chip

PRODUCT CODE: GT-STKY-AH3

For printing options or for produce transponder with different color or with other type of customization... contact us for more information:

Global Tag Srl - Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

- P +39 030 2005259
- S global-tag
- W www.global-tag.com
- M sales@global-tag.com

#### DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2016 - Global Tag Srl