ELC BFIL TFIE RFID Mg Made insues

PRODUCT DATASHEET GLOBAL TAG ROUND BEACONY (BLE)



Global Tag **ROUND BEACONY** is Beacon Bluetooth Low Energy (version 4.0 smart) tag with circle form can be used in indoor location system.

With replaceable battery can reach reading distance 50 meters.

Design to operate with iOS 7.0 and Android 4.3+ system.





MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions: Ø36mm diameter / Ø1,41in diameter Thickness: 16mm / 0,63 in Mounting System: Adhesive 3M 467 Weight: 35gr. Material: ABS Color: generally white, available on demand other colors (MOQ can be request) Class Protection: IP40 Battery type: CR2477 1000mAh. replaceable. Battery life: up to one year System-On-Chip (SoC): CC2540/CC2541 BLE 4.0 module Storage Temperature: -25°C to +50°C / -13°F to +122°F Operating Temperature: -25°C to +50°C / -13°F to +122°F Delivery format: Singulated Expected lifetime: Years in normal operating conditions

_ ELECTRONIC AND OPERATIVE PARAMETERS

Operation Frequency: 2400-2483,5MHz IEEE Standard: 802.15.1 (Bluetooth 4.0 Low Energy BLE) Transmission distance: 50meters Default Ping Rate: 500ms Ping Rate interval: 100ms to 10000ms. (step of 100ms) Support Operating System: iOS7.0 and Android 4.3+ Accurate digital RSSI

UID NUMBER AND ADVERTISING PACKET

UID Address : 6 Byte Unique identifier
Advertising Size: 30bytes
Proximity UUID: 16bytes (including in advertising packet)
Major: 2bytes (including in advertising packet)
Minor: 1byte (including in advertising packet)

www.global-tag.com



CUSTOMIZATION OPTIONS

Silk Printing : printing logo or serial number

_ INSTALLATION MODE

With 3M Adhesive: when mounting the tag with adhesive background, clean and dry the surface for obtaining maximum bond strength.

APPLICATION NOTE

Retail Marketing Indoor asset tracking

CERTIFICATIONS

iBeacon License CE Regulations (Included EN300328, EN301489, EN60950, EM62479) FCC Regulations (FCC Part 15)

__ ORDER INFORMATION

PRODUCT CODE ROUND BEACONY: GT-RNBY-BLE

For printing options or for produce transponder with different color or with other type of customization... contact us for more information: **Global Tag Srl** – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

- P +39 030 2005259
- S global-tag
- W www.global-tag.com
- M sales@global-tag.com

DISCLAIMER

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document.

Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2016 - Global Tag Srl