


DISK BEACONY (BLE)



Global Tag DISK BEACONY is a BLE (Bluetooth Low Energy 4.2) Smart Beacon designed for indoor/outdoor IoT applications.

- 31mm diameter plastic housing
- ON/OFF button with additional functions (reset, alarm)
- Battery CR2032 replaceable
- When the battery is low, two lights will flash once every 5 seconds.
- Press-fit housing closure
- Up to 200m detection distance
- iBeacon and Eddystone (UID, URL, TLM) compliant
- Sticker with Mac Address (and its QRcode) and Friendly Name on the beacon surface
- LED function for Pick to Light
- Optionally, accelerometer, temperature/humidity sensor
- Optionally, NFC integrated
- Choice between a wide range of Firmware

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS:

Dimensions: \varnothing 31mm diameter / \varnothing 1,22in diameter

Thickness: 10mm / 0.3937in

Weight: 8,2gr (including battery)

Material: PC (Polycarbonate)

Color: White (customized on request)

Class Protection: IP65

Battery type: CR2032 replaceable (Panasonic®)

Battery life: One year (with Broadcast Interval: 1 second and Tx Power: 0dB)

System-On-Chip (SoC): Nordic 52810

Storage Temperature: -15°C to +50°C / 5°F to +122°F

Operating Temperature: -15°C to +45°C / 5°F to +113°F

Delivery format: Singulated

Expected lifetime: Years in normal operating conditions

G-Sensor: ST Microelectronics mod. LIS3DH

Temperature/humidity sensor: Sensirion mod. SHT3x-DIS

ELECTRONIC AND OPERATIVE PARAMETERS:

Operation Frequency: 2400-2483,5MHz

IEEE Standard: 802.15.1 (Bluetooth 4.2 Low Energy BLE)

Transmission distance: up to 200meters

Transmission Power: 4 different Level (-23dBm / -6dBm / 0dBm / +4dBm)

Default Broadcast Interval: 1s

Broadcast interval: 100ms to 10000ms. (step of 100ms) – Except optional “Longer Broadcast Interval FW”

Support Operating System: iOS7.0 and Android 4.2+

Scan Response: Yes (max 31Byte Length), containing Battery level, Device name (11Byte), Sensors value

FCC and CE Certification

CUSTOMIZATION OPTIONS:

Housing Printing : Logo printing or serial number laser engraving

Label on surface: Label can be customized according to customer's request

Setting / Encoding: Beacons services values can be pre-set as per customer's requirement (from xls file)

Available sensors: Accelerometer and/or temperature/humidity sensor

Firmware: Different FW are available, which can be uploaded on request

APPLICATION NOTE:

Retail Marketing, Indoor Asset Tracking, Indoor Positioning, Smart Guide for museums and theme parks, Pick-to-light, Maintenance, Worker Safety

PRODUCT CODE AND ORDER INFORMATION:

GT-DKBY-BLE: Disk Beacony without sensors

GT-DKBY_A-BLE: Disk Beacony with accelerometer

GT-DKBY_TH_BLE: Disk Beacony with temperature/humidity sensor

GT-DKBY_ATH-BLE: Disk Beacony with accelerometer and with temperature/humidity sensor

For any clarification, please do not hesitate to contact us at any time:

Global Tag Srl - Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER:

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document. Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general-purpose product not designed or intended for any specific application. Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.