

RFID & NFC MINI CARD



Global Tag MINI CARD is an RFID/NFC PVC plate designed for identification and access control applications, with the option to add a strap and convert it into a wearable wristband.

The MINI CARD is available in LF and HF (including NFC) technologies, ensuring compatibility with different systems. Its compact and lightweight design allows easy handling and comfortable use when worn, even in high-frequency usage environments.

The MINI CARD + band solution is widely used for applications such as festival micropayments, camping, SPA and resort access control, and museum ticketing, where quick and reliable identification is required.

Customization options include background color selection, offset logo printing and encoding, allowing easy integration into customer systems and branding requirements.

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS:

PVC mini-card available dimensions:




Card size: 42x26mm
Hole size: 3x20mm



Card size: 40x25mm
Hole size: 3x15mm



Card size: 39x25mm
Hole size: 2x18mm



Card size: 34.5x26mm
Hole size: 3.9mm



Card size: 35x26mm
Hole size: 2x15mm



Card size: 50.8x25.4mm
Hole size: 2x15mm



Card size: 33x26mm
Hole size: 2x15mm



Card size: 38x20mm
Hole size: 2x15mm



Card size: 50.8x28mm
Hole size: 2x15mm

Strap available dimensions:



Clip: The clip of the fabric wristband can be disposable or reusable, according to the project requirements.

Material:

Mini card: PVC

Strap: fabric

Color: To be customized

Class Protection: IP68 (Totally protected against ingress of solid / Protected against long period of immersion)

Storage Temperature: -55°C + 65°C / -67°F to +149°F

Operating Temperature: -25°C + 50°C / -13°F to +122°F

Weather Ability: Very Good, including UV resistance and sea water

Delivery format: Individual

Expected lifetime: Years in normal operating conditions

CHIP SPECIFICATION AVAILABLE:

	LF 125Khz	HF 13,56MHz
Device type	N.D.	N.D.
Air interface protocol	N.D.	ISO14443 and ISO15693 and NFC
IC Type Available	TK4100, T5577, EM4200, other on request	I-Code SLIX, I-Code SLIS, Mifare Ultralight, Mifare Classic 1K, Mifare Classic 4K, Mifare Plus X 4K, Mifare Desfire 4K, STM LRI2k, Ntag213, Ntag216 other on-request
Size Inlay	18mm diameter	18mm diameter
Read Range	From 2 to 10cm	From 2 to 20cm

CUSTOMIZATION OPTIONS:

Silk Printing: 4-colors printing logo

Pre-Encoding: Customer specific encoding of EPC or User Memory (also from Database). Locking permanently or with password. Insert into Database TID code. For NFC chip encoding memory with different type of NFC (E-mail, URI etc.)

APPLICATION NOTE:

Access Control: MINI CARD, with the addition of the strap, is used for access control in many different environments as swimming-pool, aquatic park, SPA or beauty center, hotel.

Micro-Payment and ticketing: MINI CARD, with the addition of the strap, in particular with HF ISO14443 (NFC) chip, can be used for micropayment in events like festival.

Fidelity or VIP Pass

ORDER INFORMATION:

PRODUCT CODE: GT-BDGY_XXS_YYWW-xx (YYWW defines the required size; xx defined type of chip required)

Global Tag Srl – Via Zanardelli 13/A 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER:

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document. Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general-purpose product not designed or intended for any specific application. Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2025 - Global Tag Srl