

## ON-METAL HARDY\_6



Global Tag **ON-METAL HARDY\_6** is the smallest on-metal UHF tag, with good performance. Designed for indoor and outdoor environments, it is the best solution if you need to mount a transponder on a small metal surface. It can optionally be provided with 3M adhesive. It can alternatively be mounted through the little hole.

### MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

**Dimensions:** 6mm diam (0,24inch diam.) / thickness: 4mm (0,16inch)

**Mounting System:** Rivet Holes (two 1mm holes; one 2mm hole); Adhesive (3M)

**Weight:** 0,2gr.

**Material:** PCB Material

**Color:** Generally black color – Available optionally any other colors

**Class Protection:** IP67 (Totally protected against ingress of solid / Protected against short periods of immersion in water.)

**Storage Temperature:** -55°C (for 3h) to +100°C (for 2h) / -67°F (for 3h) to +230°F (for 2h) (for any other particular request contact us)

**Operating Temperature:** -25°C to +85°C / -13°F to +185°F

**Weather Ability:** Very Good, including UV resistance and sea water

**Delivery format:** Individual

**Expected lifetime:** Years in normal operating conditions

**Chemical resistance:**

No physical or performance changes in (tested up to, more hours can be):

- 200 hours Motor oil immersion

- 200 hours Salt water (salinity 10%) exposure

- 200 hours H<sub>2</sub>SO<sub>4</sub> Sulfuric acid (10% pH 2) exposure
- 24 hours NaOH Caustic Soda (10%, PH 13) exposure
- 24 hours HCl Muriatic Acid (10%) exposure
- 24 hours Na<sub>2</sub>CO<sub>3</sub> Soda Solvay
- 24 hours NH<sub>3</sub> Ammoniac (5% to 25%)

Values in the table are the best recommendations; resistance against environmental conditions depends on the combinations of all influencing factors, exposure duration and chemical concentrations. Thus, product's final suitability for certain environmental conditions is recommended to be tested. We are available for other information.

### **INSTALLATION MODE:**

**With 3M Adhesive model:** when mounting the tag with adhesive background, clean and dry the surface to get the maximum bond strength. Through the 3 holes (n.2 1mm diam. holes; n.1 2mm diam. hole)

### **CUSTOMIZATION OPTIONS:**

**Laser engraving:** serial progressive number from database, randomize number from database text and Barcode or QRCode. Other customizations on request.

**Pre-Encoding:** Customer specific encoding of EPC or User Memory (also from Database). Locking permanently or with password. Insert into Database TID code.

### **ORDER INFORMATION:**

**Standard product is made with Alien Higgs3 chip**

**PRODUCT CODE:** GT-HRDY\_6-AH3

For printing options or for produce transponder with different color or with other type of customization... contact us for more information:

**Global Tag Srl** – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

**P** +39 030 2005259

**S** global-tag

**W** www.global-tag.com

**M** sales@global-tag.com