

## REUSABLE (WITH DISPOSABLE WRAP) CABLE TIE



Global Tag **REUSABLE CABLE TIE** is a series of cable tie tags in which the RFID tag and the tail are provided separately; in this way the RFID Tag can be reused and the disposable tie can be wasted. It is available in HF 13.56Mhz, both ISO 14443 (NFC) and ISO 15693 and in UHF 860-960Mhz. Different customizations are available such as logo printing, serial number laser engraving, EPC and user memory encoding.

### MAIN FEATURES:

**Dimensions:** 28mm diameter, 4mm thickness / 33x23mm, 3,5mm thickness / 52x52mm, 4mm thickness / 49x45mm, 6mm thickness

**Material:** High Quality ABS and PE Material

**Color:** Different colors

**Class Protection:** IP68 (Totally protected against ingress of solid / Protected against long period of immersion)

**Storage Temperature:** -30°C to + 100°C

**Operating Temperature:** -25°C to + 85°C

### IC Chip:

➤ **HF/NFC Version:** Mifare Ultralight, Mifare Classic 1K, N-Tag213, N-Tag216, I-Code SLIX, others on request

➤ **UHF Version:** Alien Higgs3, Alien Higgs9, NXP U-Code8, NXP U-Code9, Monza R6, others on request

**Product Code:** GT-CBLY\_AS-XX