

RFID PVC WRISTBAND WITH CLIP SINGLE USE



Global Tag **H-WRISTBY** is the disposable wristband designed for Hospital and Healthcare applications, where the main need is represented by the tracking of patients.

Also, it is a great solution for any other applications that require a disposable wristband, such as swimming pools, fitness centers, spa and resorts.

This tag is available in LF and HF (also NFC) frequency. Different customizations are available.

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions: 247X25 mm

Mounting System: Disposable clip

Weight: 3,5 gr

Material: Soft PVC (Matt or Gloss surface)

Color: All colors

Class Protection: IP67

Storage Temperature: -40°C to +65°C / -40°F to +149°F

Operating Temperature: -25°C to +50°C / -13°F to +122°F

Delivery format: Individual or packs of 10pcs

Expected lifetime: Some years in normal operating conditions

CHIP SPECIFICATION AVAILABLE:

	LF 125Khz	HF 13,56MHz
Device type	N.D.	N.D.
Air interface protocol	N.D.	ISO14443 and ISO15693 and NFC
IC Type Available	TK4100, T5577, EM4200, other on request	NXP ICode SLI-X/-S, STM LRI2K, Texas TI2048, NXP Mifare Ultralight, NXP Mifare Classic 1KB/4KB, NXP Mifare Desfire 2KB/4KB/8KB, NXP Mifare Plus 4KB, NXP Ntag213 / Ntag216
Size Inlay	18mm diameter	18mm diameter
Read Range	From 2 to 10cm	Up to 20cm

CUSTOMIZATION OPTIONS:

Silk Printing: Serial UID, serial progressive number from database, random number from database, text, Barcode or QRCode. Other customization on request. Front side 4-colors logo printing.

Pre-Encoding: Customer specific encoding of User Memory (also from Database). On N-Tag213 chip (NFC) memory encoding (mailto, URI or other information) from database.

APPLICATION NOTE:

Hospital Patients Tracking
 SPA/Beauty center customers micropayments
 Swimming Pool/Training center access control

ORDER INFORMATION:

PPRODUCT CODE: GT-H_WRSTY-xx (xx required chipset)

For further information or customized request:

Global Tag Srl – Via Zanardelli 13/A 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com