

SUCTION CUP BEACONY (BLE)



Global Tag **SUCTION CUP BEACONY** is a BLE (Bluetooth Low Energy 4.2) Smart Beacon based on disk Beacony with special form (in silicone) designed for glasses and where removal is needed.

- Waterproof silicone housing
- ON/OFF button with additional functions (reset, alarm)
- Battery CR2032 replaceable
- Press-fit housing closure
- Up to 200m detection distance
- iBeacon and Eddystone (UID, URL, TLM) compliant
- Sticker with Mac Address (and its QRcode) and Friendly Name on the beacon surface
- LED function for Pick to Light
- Optionally, accelerometer, temperature/humidity sensor
- Optionally, NFC integrated
- Choice between a wide range of Firmwares

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS:

Dimensions: 70x37mm (max size) / 2,76x1,45in

Thickness: 33mm / 1.30in

Weight: 19,5gr (including battery)

Material: Silicone (external case) – Polycarbonate (internal case)

Color: White (customized on request)

Class Protection: IP67

Battery type: CR2032 replaceable (Panasonic®)

Battery life: One year (with Broadcast Interval: 1 second and Tx Power: 0dB)

System-On-Chip (SoC): Nordic 52810

Storage Temperature: -15°C to +50°C / 5°F to +122°F

Operating Temperature: -15°C to +45°C / 5°F to +113°F

Delivery format: Singulated

Expected lifetime: Years in normal operating conditions

G-Sensor: ST Microelectronics mod. LIS3DH

Temperature/humidity sensor: Sensirion mod. SHT3x-DIS

ELECTRONIC AND OPERATIVE PARAMETERS:

Operation Frequency: 2400-2483,5MHz

IEEE Standard: 802.15.1 (Bluetooth 4.2 Low Energy BLE)

Transmission distance: up to 200meters

Transmission Power: 4 different Level (-23dBm / -6dBm / 0dBm / +4dBm)

Default Ping Rate: 1s

Ping Rate interval: 100ms to 10000ms. (step of 100ms) – Except optional “longer broadcast interval FW”

Support Operating System: iOS7.0 and Android 4.2+

Scan Response: Yes (max 31Byte Length), containing Battery level, Device name (11Byte), Sensors value

FCC and CE Certification

CUSTOMIZATION OPTIONS:

Housing Printing : Logo printing or serial number laser engraving

Label on surface: Label can be customized according to customer's request

Setting / Encoding: Beacons services values can be pre-set as per customer's requirement (from xls file)

Available sensors: Accelerometer and/or temperature/humidity sensor

Firmware: Different FW are available, which can be uploaded on request

APPLICATION NOTE:

Retail Marketing, Outdoor Asset Tracking, Indoor Positioning, Smart Car Dealer tracking, Pick-to-light, Maintenance

PRODUCT CODE AND ORDER INFORMATION:

GT-SCPBY-BLE: Suction Cup Beacony without sensors

GT-SCPBY_A-BLE: Suction Cup Beacony with accelerometer

GT-SCPBY_TH_BLE: Suction Cup Beacony with temperature/humidity sensor

GT-SCPBY_ATH-BLE: Suction Cup Beacony with accelerometer and with temperature/humidity sensor

For any clarification, please do not hesitate to contact us at any time:

Global Tag Srl - Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER:

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document. Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general-purpose product not designed or intended for any specific application. Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.