



RELEASABLE CABLY



Global Tag **RFID RELEASABLE CABLY** is a reusable RFID cable-tie tag featuring a special locking mechanism that allows the tail to be released without damaging the tag. This design enables the RFID tag to be installed, removed and reused several times, making it suitable for applications requiring temporary or repeated identification.

RFID RELEASABLE CABLY is available in HF 13.56 MHz, supporting both ISO 14443 / NFC and ISO 15693 standards, as well as in UHF 860–960 MHz. It is particularly suitable for asset management, logistics, maintenance, equipment identification and industrial tracking applications.

Different customization options are available, including logo printing, laser-engraved serial numbers, EPC encoding and User Memory encoding, allowing the tag to be adapted to specific identification and traceability requirements.

MECHANICAL AND ENVIRONMENTAL SPECIFICATIONS:

Dimensions:

- **HF/NFC/UHF Version:** 335x30mm (including 282mm tail length) / thickness 1cm
- **Only UHF Version:** 330x75mm (including 282mm tail length) / thickness 1cm

Mounting System: Cable-tie

Weight: Depends on the selected model/size

Material: High Quality ABS and PE Material

Color: Generally dark grey – Available optionally any other colors

Class Protection: IP68

Storage Temperature: -30°C to + 100°C / -22°F to +212°F

Operating Temperature: -25°C to + 85°C / -13°F to 185°F

Weather Ability: Very Good, including UV resistance and sea water

Delivery format: Individual

Expected lifetime: Years in normal operating conditions

Chemical resistance:

No physical or performance changes in (tested up to, more hours can be):

- 200 hours Motor oil immersion
- 200 hours Salt water (salinity 10%) exposure
- 200 hours H₂SO₄ Sulfuric acid (10% pH 2) exposure
- 24 hours NaOH Caustic Soda (10%, PH 13) exposure
- 24 hours HCl Muriatic Acid (10%) exposure
- 24 hours Na₂CO₃ Soda Solvay
- 200 hours NH₃ Ammoniac (5% to 25%)

Values in the table are the best recommendations; resistance against environmental conditions depends on the combinations of all influencing factors, exposure duration and chemical concentrations. Thus, product's final suitability for certain environmental conditions is recommended to be tested. We are available for other information.

AVAILABLE CHIP SPECIFICATION:

	HF 13,56MHz	UHF 860-960MHz
Device type	N.D.	Class 1 Gen 2
Air interface protocol	ISO14443 and ISO15693 and NFC	ISO18000-63
IC Type Available	I-Code SLIX, I-Code SLIS, Mifare Ultralight, Mifare Classic 1K, Mifare Classic 4K, Mifare Plus X 4K, Mifare Desfire 4K, STM LRI2k, Ntag203, others on-request	Alien Higgs3, Alien Higgs 4, NXP U-Code8, NXP U-Code9 others on-request
Size Inlay	It depends on selected IC chip	38x17mm
Read Range	From 2 to 50cm	Up to 4meters

CUSTOMIZATION OPTIONS:

Printing laser engraving: Serial UID, serial progressive number from database, randomize number from database text and Barcode or QRCode. Other customization on required.

Pre-Encoding: Customer specific encoding of EPC or User Memory (also from Database). Locking permanently or with password. Insert into Database TID code.

INSTALLATION MODE:

Wrap the tag like a cable tie and cut off the leftover part

APPLICATION NOTE:

Asset management: **CABLY** can be used to track and manage corporate asset even when they are outdoors or in harsh conditions. Thanks to the long wrappe, it can be easily applied also on big objects without possibility to remove it.

Waste bin management: **CABLY** can be applied on waste bins both plastic or metallic material; this Qu-id help to simplify project and help to have only one tag for all type of waste bins.

Maintenance: **CABLY** is a strong tag designed to improve maintenance services with easy installation on all surface.

Cables Tracking: **CABLY**, with its cable-tie form, is a great solution for the tracking of cables and optical fibers

ORDER INFORMATION:

Standard product is made with Alien Higgs3 chip

PRODUCT CODE: GT- CBLY_RE-XX (XX defines the selected IC chip)

For printing options or for produce transponder with different color or with other type of customization... contact us for more information:

Global Tag Srl – Via Zanardelli 13/A, 25062 Concesio (BS) - Italy

P +39 030 2005259

S global-tag

W www.global-tag.com

M sales@global-tag.com

DISCLAIMER:

The information in this document is subject to change without notice. Global Tag assumes no responsibility for any errors that may appear in this document. Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general-purpose product not designed or intended for any specific application. Global Tag Srl or its subsidiaries are not responsible for the performance or support of third party products and does not make any representations or warranties whatsoever regarding quality, reliability, functionality, or compatibility of these devices or products.

© Copyright 2025 - Global Tag Srl